


PRECURED RETREAD - INNER/OUTER ENVELOPE SYSTEM

DEE



SHORT SKIRT ENVELOPE,
FOR INNER/OUTER PRECURED
VULCANIZATION SYSTEM



CODE	SPECIFICATIONS AXB (MM, IN)	TIRES SUGGESTED
DEE-12	1220x730	315/75R24.5, 365/80R22.5, 385/75R22.5, 445/65R22.5
	48x29	11.00R24, 12.00R24, 13.00R20, 13.5R24.5, 15R22.5
DEE-11/12	1140x730	295/80R24.5, 305/70R24.5, 305/75R24.5, 305/85R22.5, 385/65R22.5, 425/65R22.5, 445/50R22.5
	45x29	10.00R22, 11.00R22, 11R24.5, 12.00R20, 12.00R22, 12R24.5, 12.5R22.5, 13.5R22.5, 15R22.5
DEE-11	1090x685	275/80R24.5, 285/75R24.5, 295/80R22.5, 305/75R22.5, 315/75R22.5, 315/80R22.5
	43x27	10.00R20, 11.00R20, 11R22.5, 12R22.5, 13/80R20
DEE-10	1040x630	275/80R22.5, 295/75R22.5, 305/70R22.5, 315/70R22.5
	41x25	9.00R20, 10R22.5, 12/70R22.5, 12/80R20
DEE-9	980x555	245/75R22.5, 265/75R22.5, 275/70R22.5, 305/60R22.5, 305/70R19.5
	38x22	8.25R20, 9R22.5
DEE-8	970x535	235/80R22.5, 255/70R22.5, 265/70R22.5
	38x21	7.00R20, 7.50R20, 8R22.5, 9.5R19.5, 10.00R15, 11R17.5
DEE-78	945x505	285/70R19.5, 300R15
	37x20	6.50R20, 9.5R17.5, 9R19.5, 10R16.5, 10R17.5
DEE-77	900x480	245/70R19.5, 265/70R19.5
	35x19	7.50R18, 8R19.5, 8.25R17, 8.75R16.5, 9.00R15, 9.00R16, 9.5R16.5
DEE-76	822x480	215R15, 215/85R16, 225/70R19.5, 225/75R17.5, 235/70R19.5, 235/75R17.5, 245/65R19.5, 245/70R17.5, 245/75R16, 255/75R15, 265/75R16
	32x19	7.00R16, 7.00R18, 7.50R15, 7.50R16, 7.50R17, 8R16.5, 8R17.5, 8.25R15, 8.25R16, 8.5R17.5
DEE-7	790x480	205R16, 215R16, 215/70R15, 215/75R17.5, 225/70R16, 235/70R16, 235/75R15, 245/70R16, 250R15
	31x19	6.50R16, 7.00R15, 7R17.5, 28x9x15
DEE-6	735x380	185R16, 195R16, 205/75R15, 205/75R16, 215R14, 215/75R16, 225/75R15, 225/70R16
	29x15	6.00R16, 7.00R12, 27x10x12
DEE-4	685x380	175/75R16, 185R14, 185/75R14, 185R15, 195R14, 195/75R14, 205R14, 205/75R14
	27x15	7.50R10, 23x10x12
DEE-2	645x355	165R14, 165/70R14, 175R14, 175/70R14
	25x14	
DEE-1	585x310	165/70R13, 165/80R13, 175/70R13
	23x12	

DMT



NEW

CODE	SPECIFICATIONS AXB (IN)	TIRES SUGGESTED
DMT-45	45x29	295/80R24.5, 305/75R24.5, 305/85R22.5, 315/80R22.5, 315/75R22.5, 385/65R22.5
		12R24.5, 11R24.5, 13.5R22.5, 12.5R22.5, 12.75R22.5, 12R22.5, 12.00R22, 11.00R22, 10.00R22, 14/80R20, 12.00R20
DMT-43	43x27	285/75R24.5, 275/80R24.5, 295/75R22.5, 295/80R22.5, 305/70R22.5, 305/75R22.5, 315/70R22.5
		11R22.5, 12/70R22.5, 10.00R20, 13/80R20
DMT-41	41x25	275/80R22.5, 10R22.5, 9.00R20, 12/80R20
		9.00R20, 12/80R20

MOLDED OUTER ENVELOPES WITH SHORT SKIRT

DOBERMANN




劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

PRECURED RETREAD - INNER/OUTER ENVELOPE SYSTEM

DEI



INNER ENVELOPE FOR PRECURED VULCANIZATION PROCESS.


CODE	SPECS AXBXC (MM, IN)	TIRES SUGGESTED
DEI-1300x500	1300x500x900	425/65R22.5, 445/65R22.5
	51x19,5x35,5	12.00R24, 16.5R22.5, 18R22.5
DEI-1200x560	1200x560x870	365/80R22.5, 385/65R22.5, 385/75R22.5, 305/85R22.5
	47x22x34,5	11.00R24, 11R24.5, 12R24.5
DEI-1160x480	1160x480x860	275/80R24.5, 305/70R24.5, 315/75R22.5, 365/65R22.5, 425/55R19.5, 445/50R22.5, 315/80R22.5
	45,5x19x34	12.00R20, 13.00R20, 13/80R20, 14/80R20, 12.00R22, 12.5R22.5, 13R22.5, 15R22.5
DEI-1100x480	1100x480x860	275/70R24.5, 295/80R22.5, 315/70R22.5, 305/75R22.5, 365/65R22.5
	43,5x19x34	10.00R22, 11.00R20, 11.00R22, 12R22.5
DEI-1060x480	1060x480x810	275/80R22.5, 295/75R22.5, 305/70R22.5
	42x19x32	11R22.5, 12/80R20
DEI-1010x480	1010x480x790	235/80R22.5, 245/75R22.5, 255/70R22.5, 265/70R22.5, 265/75R22.5, 275/70R22.5, 285/70R22.5, 305/60R22.5, 305/70R22.5
	40x19x31	9.00R20, 9R22.5, 10.00R20, 10R22.5, 12/70R22.5
DEI-960x440	960x440x690	265/70R19.5, 285/70R19.5
	38x17,5x27	7.50R20, 8R22.5, 8.25R20, 9.5R19.5
DEI-880x380	880x380x675	225/70R19.5, 235/70R19.5, 235/75R19.5, 245/70R19.5, 245/65R19.5, 265/75R16, 300R15
	34,5x15x26,5	6.50R20, 7.00R20, 7.50R18, 8R16.5, 8R19.5, 8.25R15, 8.25R16, 8.5R17.5, 8.75R16.5, 9.00R15, 9.00R16, 9R19.5, 9.5R16.5, 9.5R17.5, 10.00R15, 10R16.5, 10R17.5
DEI-780x400	780x400x640	205R16, 205/75R17.5, 215R16, 215/75R16, 215/75R17.5, 215/85R16, 225/70R16, 225/75R16, 225/75R17.5, 235/70R16, 235/75R17.5, 245/70R16, 245/75R16, 245/70R17.5
	30,5x16x25	7.00R16, 7R17.5, 7.00R18, 7.50R15, 7.50R16, 7.50R17, 8R17.5, 9R17.5
DEI-700x315	700x315x570	175/75R16, 185R14, 185/75R14, 185R15, 185R16, 185/75R16, 195R14, 195/75R14, 195R16, 195/75R16, 205R14, 205/75R14, 205R15, 205/75R15, 205/75R16, 215R14, 250R15
	27,5x12,5x22,5	6.00R16, 6.50R16, 7.00R15

DVB



CODE	SPECIFICATIONS AXB (MM, IN)	TIRES SUGGESTED
DVB-155	1370x155	Super Single / Truck
	54x6	
DVB-115	752x115	Light Truck / Van
	29,5x4,5	


WICKING PADS FOR PRECURED VULCANIZATION PROCESS



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD. No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.
Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

PRECURED RETREAD - ARC SYSTEM

DAS



CODE SPECIFICATIONS AXB (IN)

TIRES SUGGESTED

CODE	SPECIFICATIONS AXB (IN)	TIRES SUGGESTED
DAS-L11/12	44x38	305/80R24.5, 315/75R24.5 12R22.5, 12.5R22.5
DAS-11/12	44x36	295R80R24.5, 305/85R22.5 11.00R22, 11R24.5
DAS-L11	42x36	285/80R24.5, 305/70R24.5, 305/75R24.5, 315/75R22.5, 315/80R22.5 10.00R22
DAS-11	42x34	275/80R24.5, 285/75R24.5, 295/80R22.5, 305/70R24.5 10.00R22
DAS-L10	40x34	305/70R22.5, 315/70R22.5 10.00R20, 12/70R22.5
DAS-10	40x32	275/80R22.5, 295/75R22.5 10R22.5

EXTERN ENVELOPE FOR ARC SYSTEM

DSR



CODE TIRES SUGGESTED

CODE	TIRES SUGGESTED
DSR-24/24.5	24", 24.5"
DSR-22/22.5	22", 22.5"
DSR-20	20"
DSR-19.5	19.5"

RUBBER RING FOR ARC SYSTEM

DVB




CODE SPECIFICATIONS AxB (mm, in)

TIRES SUGGESTED

CODE	SPECIFICATIONS AxB (mm, in)	TIRES SUGGESTED
DVB-155	1370x155 54x6	Super Single / Truck
DVB-115	752x115 29,5x4,5	Light Truck / Van

WICKING PADS FOR PRECURED VULCANIZATION PROCESS



DOBERMANN



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.


Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

PRECURED RETREAD - OUTER ENVELOPE WITH RIM SYSTEM

DEE-L



LONG SKIRT ENVELOPE, FOR
PRECURED VULCANIZATION SYSTEM
WITH RIM-FLANGES



CODE	SPECIFICATIONS AXB (MM, IN)	TIRES SUGGESTED
DEE-L12	1220x810	315/75R24.5, 365/80R22.5, 385/75R22.5, 445/65R22.5
	48x32	11.00R24, 12.00R24, 13.00R20, 13.5R24.5, 15R22.5
DEE-L11/12	1140x810	295/80R24.5, 305/70R24.5, 305/75R24.5, 305/85R22.5, 385/65R22.5, 425/65R22.5, 445/50R22.5
	45x32	10.00R22, 11.00R22, 11R24.5, 12.00R20, 12.00R22, 12R24.5, 12.5R22.5, 13.5R22.5, 15R22.5
DEE-L11	1090x760	275/80R24.5, 285/75R24.5, 295/80R22.5, 305/75R22.5, 315/75R22.5, 315/80R22.5
	43x30	10.00R20, 11.00R20, 11R22.5, 12R22.5, 13/80R20
DEE-L10	1040x630	275/80R22.5, 295/75R22.5, 305/70R22.5, 315/70R22.5
	41x28	9.00R20, 10R22.5, 12/70R22.5, 12/80R20
DEE-L9	980x635	245/75R22.5, 265/75R22.5, 275/70R22.5, 305/60R22.5, 305/70R19.5
	38x25	8.25R20, 9R22.5
DEE-L8	970x610	235/80R22.5, 255/70R22.5, 265/70R22.5
	38x24	7.00R20, 7.50R20, 8R22.5, 9.5R19.5, 10.00R15, 11R17.5
DEE-L78	945x585	285/70R19.5, 300R15
	37x23	6.50R20, 9.5R17.5, 9R19.5, 10R16.5, 10R17.5
DEE-L77	900x555	245/70R19.5, 265/70R19.5
	35x22	7.50R18, 8R19.5, 8.25R17, 8.75R16.5, 9.00R15, 9.00R16, 9.5R16.5
DEE-L76	822x555	215R15, 215/85R16, 225/70R19.5, 225/75R17.5, 235/70R19.5, 235/75R17.5, 245/65R19.5, 245/70R17.5, 245/75R16, 255/75R15, 265/75R16
	32x22	7.00R16, 7.00R18, 7.50R15, 7.50R16, 7.50R17, 8R16.5, 8R17.5, 8.25R15, 8.25R16, 8.5R17.5
DEE-L7	790x555	205R16, 215R16, 215/70R15, 215/75R17.5, 225/70R16, 235/70R16, 235/75R15, 245/70R16, 250R15
	31x22	6.50R16, 7.00R15, 7R17.5, 28x9x15
DEE-L6	735x460	185R16, 195R16, 205/75R15, 205/75R16, 215R14, 215/75R16, 225/75R15, 225/70R16
	29x18	6.00R16, 7.00R12, 27x10x12
DEE-L4	685x460	175/75R16, 185R14, 185/75R14, 185R15, 195R14, 195/75R14, 205R14, 205/75R14
	27x18	7.50R10, 23x10x12
DEE-L2	645x430	
	25x17	165R14, 165/70R14, 175R14, 175/70R14
DEE-L1	585x385	
	23x15	165/70R13, 165/80R13, 175/70R13

CODE	SPECIFICATIONS AXB (IN)	TIRES SUGGESTED
DMT-L45	45x31	295/80R24.5, 305/75R24.5, 305/85R22.5, 315/80R22.5, 315/75R22.5, 385/65R22.5
		12R24.5, 11R24.5, 13.5R22.5, 12.5R22.5, 12.75R22.5, 12R22.5, 12.00R22, 11.00R22, 10.00R22, 14/80R20, 12.00R20
DMT-L43	43x29	285/75R24.5, 275/80R24.5, 295/75R22.5, 295/80R22.5, 305/70R22.5, 305/75R22.5, 315/70R22.5
		11R22.5, 12/70R22.5, 10.00R20, 13/80R20
DMT-L41	41x27	275/80R22.5, 10R22.5, 9.00R20, 12/80R20
		9.00R20, 12/80R20

DMT-L

NEW



MOLDED OUTER ENVELOPES WITH LONG SKIRT



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

PRECURED RETREAD - OUTER ENVELOPE WITH RIM SYSTEM

CODE TIRES SUGGESTED

DPB-24	275/80R24.5, 285/75R24.5, 285/80R24.5, 295/80R24.5, 305/70R24.5, 305/75R24.5, 305/80R24.5, 315/75R24.5
DPB-22L	305/85R22.5, 315/75R22.5, 315/80R22.5, 365/6 5R22.5
DPB-22	295/80R22.5, 315/70R22.5
DPB-22S	275/80R22.5, 295/75R22.5, 305/70R22.5
DPB-20L	11.00R20, 12/80R20, 12.00R20, 13.00R20
DPB-20M	285/70R19.5, 305/70R19.5
DPB-20S	7.00R20, 7.50R20, 8.25R20
DPB-19.5	225/70R19.5, 235/70R19.5, 235/75R19.5, 245/65R19.5, 245/70R19.5, 265/70R19.5
DPB-17.5	205/75R17.5, 215/75R17.5, 225/75R17.5, 235/75R17.5, 245/70R17.5
DPB-16	215/85R16, 245/70R16, 245/75R16, 250R15, 255/75R15, 185R16, 195R16, 195/75R16, 205/75R16, 215/75R16, 225/75R16, 235/70R16, 205R16, 215R15, 215R16, 225/75R15, 235/75R15

CURING TUBE FOR PRECURED VULCANIZATION PROCESS

DPB




CODE SPECIFICATIONS AXBXS (MM, IN) TIRES SUGGESTED

DFL-24R8.5	170x119x216 6,7x4,7x8,5	Rim Diameter 24", Width 8.5"
DFL-22.5R9.0	196x146x245 7,7x5,7x9,6	Rim Diameter 22", Width 9.0"
DFL-22R8.5	170x120x220 6,7x4,7x8,7	Rim Diameter 22", Width 8.5"
DFL-20R8.0	160x110x201 6,3x4,3x7,9	Rim Diameter 20", Width 8.0"
DFL-20R7.5	150x90x193 5,9x3,5x7,6	Rim Diameter 20", Width 7.5"
DFL16R7.0	125x85x170 4,9x3,4x6,7	Rim Diameter 16", Width 7.0"

FLAPS FOR BOTH PRECURED AND MOLD VULCANIZATION PROCESS

DFL




CODE SPECIFICATIONS AXB (MM, IN) TIRES SUGGESTED

DVB-155	1370x155 54x6	Super Single / Truck
DVB-115	752x115 29,5x4,5	Light Truck / Van

WICKING PADS FOR PRECURED VULCANIZATION PROCESS

DVB



 **DOBERMANN**



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com




NEW

DEC

CODE	SPECIFICATIONS AXB (IN)	TIRES SUGGESTED
DEC-45	45x29	295/80R24.5, 305/75R24.5, 305/85R22.5, 315/80R22.5, 315/75R22.5, 385/65R22.5 12R24.5, 11R24.5, 13.5R22.5, 12.5R22.5, 12.75R22.5, 12R22.5, 12.00R22, 11.00R22, 10.00R22, 14/80R20, 12.00R20
DEC-43	43x27	285/75R24.5, 275/80R24.5, 295/75R22.5, 295/80R22.5, 305/70R22.5, 305/75R22.5, 315/70R22.5 11R22.5, 12/70R22.5, 10.00R20, 13/80R20
DEC-41	41x25	275/80R22.5, 10R22.5, 9.00R20, 12/80R20 9.00R20, 12/80R20

OUTER ECOLOPE



DEI-EC

CODE	SPECS AXBXC (MM)	TIRES SUGGESTED
DEI-EC1200x560	1200x560x870 47x22x34,5	365/80R22.5, 385/65R22.5, 385/75R22.5, 305/85R22.5 11.00R24, 11R24.5, 12R24.5
DEI-EC1160x480	1160x480x860 45,5x19x34	275/80R24.5, 305/70R24.5, 315/75R22.5, 365/65R22.5, 425/55R19.5, 445/50R22.5, 315/80R22.5 12.00R20, 13.00R20, 13/80R20, 14/80R20, 12.00R22, 12.5R22.5, 13R22.5, 15R22.5
DEI-EC1100x480	1100x480x860 43,5x19x34	275/70R24.5, 295/80R22.5, 315/70R22.5, 305/75R22.5, 365/65R22.5 10.00R22, 11.00R20, 11.00R22, 12R22.5
DEI-EC1060x480	1060x480x810 42x19x32	275/80R22.5, 295/75R22.5, 305/70R22.5 11R22.5, 12/80R20
DEI-EC1010x480	1010x480x790 40x19x31	235/80R22.5, 245/75R22.5, 255/70R22.5, 265/70R22.5, 265/75R22.5, 275/70R22.5, 285/70R22.5, 305/60R22.5, 305/70R22.5 9.00R20, 9R22.5, 10.00R20, 10R22.5, 12/70R22.5


INNER ECOLOPE



DVB-EC


CODE	SPECIFICATIONS AxB (mm, in)	TIRES SUGGESTED
DVB-EC155	1370x155 54x6	Super Single / Truck
DVB-EC115	752x115 29,5x4,5	Light Truck / Van

WICKING PADS FOR PRECURED VULCANIZATION PROCESS





NEW



CODE	SPECIFICATIONS AXB (IN)	TIRES SUGGESTED
DEC-L45	45x31	295/80R24.5, 305/75R24.5, 305/85R22.5, 315/80R22.5, 315/75R22.5, 385/65R22.5 12R24.5, 11R24.5, 13.5R22.5, 12.5R22.5, 12.75R22.5, 12R22.5, 12.00R22, 11.00R22, 10.00R22, 14/80R20, 12.00R20
DEC-L43	43x29	285/75R24.5, 275/8024.5, 295/75R22.5, 295/80R22.5, 305/70R22.5, 305/75R22.5, 315/70R22.5 11R22.5, 12/70R22.5, 10.00R20, 13/80R20
DEC-L41	41x27	275/80R22.5, 10R22.5, 9.00R20, 12/80R20 9.00R20, 12/80R20

OUTER ECOLOPE WITH LONG SKIRT



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

MOLD RETREAD - CURING TUBE SYSTEM




CODE	TIRES SUGGESTED
DMB-38L	20.8R38
DMB-38M	16.9R38, 18.4R38
DMB-38	14.9R38, 15.5R38
DMB-38S	12.4R38, 13.6R38
DMB-34	14.9R34, 16.9R34, 18.4R34
DMB-30	14.9R30, 16.9R30, 18.4R30
DMB-28	14.9R28, 16.9R28, 18.4R28
DMB-25	15.5R25, 16.0R25, 17.5R25, 18.0R25
DMB-24L	14.9R24, 16.4R24
DMB-24M	KM24, 13.00R24, 14.00R24
DMB-24	11R24.5, 12.00R24, 285/75R24.5
DMB-24S	11.2R24, 12.4R24
DMB-22L	11.00R22, 12.00R22, 12R22.5, 315/75R22.5, 315/80R22.5
DMB-22	10.00R22, 11.00R22.5, 295/75R22.5, 295/80R22.5, 305/75R22.5
DMB-22S	9R22.5, 10R22.5, 275/70R22.5, 275/80R22.5, 295/70R22.5
DMB-20L	12.00R20, 13.00R20
DMB-20M2	11.00R20
DMB-20M1	10.00R20, 12/80R20
DMB-20M	9.00R20, 12/70R20
DMB-20S1	8.25R20
DMB-20S	7.00R20, 7.50R20
DMB-19.5	265/70R19.5, 305/70R19.5 8R19.5, 9R19.5, 9.5R19.5
DMB-17.5	205/75R17.5, 215/75R17.5, 235/65R18 7.00R18, 7.50R18, 9.5R17.5, 11R17.5
DMB-16	205R16, 215/85R16, 245/70R16 6.00R16, 6.50R16, 7.00R16, 7.50R16, 8.25R16, 9.00R16, 12R16.5

CURING TUBE FOR MOLD VULCANIZATION PROCESS



CODE	SPECIFICATIONS AXBXS (MM, IN)	TIRES SUGGESTED
DFL-24R8.5	170x119x216 6,7x4,7x8,5	Rim Diameter 24", Width 8.5"
DFL-22.5R9.0	196x146x245 7,7x5,7x9,6	Rim Diameter 22", Width 9.0"
DFL-22R8.5	170x120x220 6,7x4,7x8,7	Rim Diameter 22", Width 8.5"
DFL-20R8.0	160x110x201 6,3x4,3x7,9	Rim Diameter 20", Width 8.0"
DFL-20R7.5	150x90x193 5,9x3,5x7,6	Rim Diameter 20", Width 7.5"
DFL16R7.0	125x85x170 4,9x3,4x6,7	Rim Diameter 16", Width 7.0"

FLAPS FOR BOTH PRECURED AND MOLD VULCANIZATION PROCESS



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

MOLD RETREAD - BLADDER SYSTEM

DCB

NEW



CODE	H (MM, IN)	A (MM, IN)	B (MM, IN)	C (MM, IN)	D (MM, IN)	TIRES SUGGESTED	WEIGHT (KG, LBS)
DCB-1 (6299)	330	323	217	22	12,5	135-145/13	3,70
	12,87	12,597	8,463	0,858	0,488		8,14
DCB-2 (6228)	346,5	386	218	21	12,5	155-165/13	4,40
	13,51	15,05	8,50	0,82	0,49		9,68
DCB-3 (6297)	447	398	245	21	12,5	Light Truck / Van	5,70
	17,43	15,52	9,56	0,82	0,49		12,54
DCB-28 (2895)	625	600	380	25,5	12,7	Truck	15,50
	24,38	23,40	14,82	0,99	0,50		34,10

CURING BLADDER FOR BOM TYPE PRESSES



劉坤貿易有限公司
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com