

# OTR TIRE BUFFERS



	Minimum Tire Size	Maximum Tire Size
AKR510REX	14. 00R24"	50/65R51"
AKR630REX	29. 50R25"	59/80R63"

## MODEL: AKR510REX, AKR630REX CNC BUFFER

### OPTIONAL FEATURES

Manual Arm

Additional Bead Plates

Conveyor Belt

### TECHNICAL FEATURES

CNC controlled OTR (9 axis) peeling, buing, extruder building and regrooving machine

18 degree inclined main frame

Hydraulic tire chucking, centering through interchangeable spacers

Central lifter for loading/ unloading

AKR510REX CNC Buffer can also be offered with the following optional features:

AKR510CR CNC Buffer (Peeling/Buffering/Regrooving)

AKR510R CNC Buffer (Regrooving)

AKR510EX CNC Buffer (Extruder Building)

AKR630REX CNC Buffer can also be offered with the following optional features:

AKR630REX CNC Buffer (Peeling/Buffering Regrooving)

AKR630R CNC Buffer (Regrooving)

AKR630EX CNC Buffer (Extruder Building)



劉坤貿易有限公司  
LIEW KOON MARKETING SDN. BHD.

No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com

