

TRUCK TIRE BUFFERS



MODEL: AKR550
CUSHION GUM EXTRUDER
WITH TREAD BUILDER

TECHNICAL SPECIFICATION

Buffing Range: 7.50 R 15 - 12.00 R 24
Minimum Tire Diameter: 700mm (27.5")
Maximum Tire Diameter: 1450mm (57")
Maximum Tire Width: 450mm (17.7")

TECHNICAL FEATURES

Suitable for truck tire cushion gum building
up to 445/65R \times 22.5" size tires
Extrusion tire width range: 140-450mm (5.5"-17.7")
Capacity: 3-5 min/tire (including building)
Standard wingforms: 3 standard sets
Extruder Unit: Screw and barrel system
Building unit included
Temperature control unit

OTHER SPECIFICATIONS

Total power: 30kW
Working pressure: 8 bar (120psi)
CE Certified

OPTIONAL FEATURES

Chiller Unit (6000 kcal/hr capacity)

HARDWARE & CONTROL FEATURES

9" panel screen with touch pad panel
Remote access to PLC via internet
Tire holding mechanism: Expandable hub and rim
(20-22.5 \times 9" size included)
Linear move tire positioning
supply voltage 380V50 Hz
Manual and automatic use



No. 27, Jalan 7/3, Taman Industri Selesa Jaya, 43300 Balakong, Selangor Darul Ehsan, Malaysia.

LIEW KOON MARKETING SDN. BHD. Tel: 6 03-8962 3163 & 8962 3168 Fax: 6 03-8962 2311 E-mail: sales@liewkoon.com.my Web: www.liewkoon.com